

UNITED ALLOYS
RESEARCH & DEVELOPMENT INC.

125 BLACKSTONE AVE.

JAMESTOWN, NY
1-800-356-WELD

454XL

SETTING THE NEW STANDARD

Penetrating Lubricant with MICRO TEFLON

DESCRIPTION

454XL is an excellent penetrating lubricant that contains PTFE for added lubricity during extreme temperatures. 454XL is recommended on any surface that slips, slides, twists, pivots or moves.

FEATURES AND BENEFITS

454XL is a high tech formulation of specialized oils blended with micron-sized PTFE to provide excellent long lasting lubrication and penetration. This unique formula provides long lasting lubrication, penetrates and defends against corrosion, dissolves grease and grime, and continues to work in extreme temperatures. (-55°F to 475°F). Provides superior corrosion protection on all metal surfaces (passes 60+ days ASTM D-1748 humidity cabinet test). 454xl does not contain chlorinated solvents which are being prohibited by companies due to potential health hazards.

APPLICATIONS AND USES

454XL is exceptional for use on vehicles, industrial machines, motors, shop equipment, large machinery, nuts and bolts, hinges, roller bearings, conveyors or pulleys, electric motors, gears, and other sliding or turning parts. You will find a need for 454XL in automotive repair shops, airport terminals, motorcycle dealers, machine shops, machinery manufacturers, trucking companies, metal fabricating shops, tool and die shops, and much more.

DIRECTIONS FOR USE

Shake well before using. Spray liberally on frozen or corroded part. Let stand for several minutes to allow thorough penetration. Reapply for long-lasting protection.

SIZE / AVAILABILITY

20 oz. Aerosol
Net Weight 15 oz.
12 per case

EXTREME DUTY 454XL