

# HEAT SHIELD GEL

**DAMAGE CONTROL GEL  
SHIELDS SURFACES AND PARTS FROM  
ADVERSE HEAT EFFECTS.**

## APPLICATIONS AND USES

\*PROTECT SEALS \*SPATTER SCREEN FOR WELDING \*SMALL FIRE CONTROL  
\*GENERAL BURN GEL \*FLAME BARRIER WHEN BRAZING \*SOLDERING AID  
\*SHIELDS FLAMMABLE SURFACES \*PROTECTS PAINTED AREAS  
\*HELPS WITH WARPAGE ON THIN PARTS \*PROTECTS PLASTIC PARTS  
\*CONTROLS HEAT  
\*\*AND MANY MANY MORE!!!

## GENERAL CHARACTERISTICS

UNIQUE HEAT SHIELDING SPRAY THAT IS SAFE NON TOXIC AND HARM-LESS TO THE SKIN. EVAPORATES QUICKLY TO REDUCE CLEANUP. WILL NOT DRIP OR SAG ON OUT OF POSITION SURFACES. WILL NOT CONTAMINATE SURROUNDING AREA.



## PROCEDURE

SPRAY LIBERAL AMOUNT OF HEAT SHIELD GEL AROUND AREAS TO BE SHIELDED LET SET FOR 10 SECONDS. AFTER USE SIMPLY WIPE AWAY OR ALLOW TO EVAPORATE.



## AVAILABLE IN:

32 OZ BOTTLES 1- 29.00EA 2 -24.50EA 6-22.00EA

United Alloys R&D Inc  
716-488-2275  
1-800-356-WELD(9353)  
www.unitedalloysrd.com  
unitedalloys@netsync.net  
125 Blackstone Ave,  
Jamestown, NY 14701